



WipeEx® SA120

Aqueous pH-neutral ready to use detergent for the machine cleaning with fleece for underscreen cleaning in screen printers

Part No. 090616-2 // Content: 2 x 5 l

CLEANING TECHNOLOGY

Made in Germany



Application overview

The cleaner is ready for use, can be used both directly in the cleaning tank of screen printers, as well as for the manual cleaning of screens and stencils.

Technical data	
Color	transparent
pH-value at 20 °C	neutral (water free)
Conductance at 20 °C	> 100 µS/cm
Flash point	> 88 °C
VOC content	< 20 %
Water solubility	easily soluble
Application	pure
Application temperature	20 - 45 °C
Storing (in original container)	10 - 30 °C
CLP / GHS	not classified as hazardous
WipeEx® SA 120 cleans quickly, thoroughly and with best possible material protection SMD adhesive and SMD paste of technical screens, stencils, PumpPrints.	

Contaminations	
Adhesive / Glue	++
Solder paste	++
Flux	—
Thermal compounds	—
Grease, Oil	—
Coating / Varnishing	—
Machine Technologies	
Spray-in-air systems	—
Spray-in-immersion systems	—
Air-in-immersion systems	—
Screen printer / cleaning unit	++
Manual application	++
<p>++ = ideal for application, + = recommended, o = optionally applicable, — = not recommended</p> <p>Note: The spreadsheet only shows a general overview of the product specifications.</p> <p>Cleaning tests are reasonable to determine the optimum cleaner configuration. Such tests may be carried out directly at the kolb demonstration center in Willich / Germany or Shanghai / China or can be initiated by contacting your local kolb partner.</p>	

kolb WipeEx® SA120 is compliant with all worldwide legal regulations and directives (REACH, RoHS, TSCA etc.) on the basis of own internal checks, analyses provided by suppliers and / or material certifications of the raw materials used in the production of kolb Cleaning Technology GmbH.