



DeSealing prefix filter

Special filter element to protect machine filter systems from coarse varnish residues in case of coating carrier cleaning.

Part numbers:

0905PSE3-90DS (PSE300-HD/VS/ML-RS/2VL/2HD)

0905AQ5-90DS (AQUBE®/PSE5)

0905AQ7-90DS (AQUBE®/PSE7)

0905AQ9-90DS (AQUBE®/PSE9)



Application

During a coating carrier machine cleaning process of carriers sealed with **kolb** CarrierSeal® or of chemical paint-stripping with **kolb** RemoCoat® the applied cleaning system must have a "DeSealing" prefix filter insert option. Since the coating residues do not totally dissolve but separate, it protects the internal filter system of the machine from clogging.

The prefix filter unit is available as an option ex factory and can also be easily retrofitted to existing machines.

The systems marked purple in the table on the right are optimally suited for coating stripping with RemoCoat SG or the the cleaning of coating carriers processed with **kolb** CarrierSeal®.

Stripped paint residues are collected by the prefix filter unit and can be removed after the process with a wet vacuum cleaner.

Attention: Chemical paint-stripping with **kolb** RemoCoat® SG must be executed in high temperature versions of the respective cleaning systems in a especially designed 4Step process.

Compatibility

	AQUBE® LH5
	AQUBE® LH7
	AQUBE® XH5
	AQUBE® XH7
	AQUBE® XH9
	AQUBE® XV7
	AQUBE® XV9
	AQUBE® PH7
	AQUBE® MH5
	AQUBE® MH7
	AQUBE® MH9
	AQUBE® MV8 sTWIN
	AQUBE® MV9 QUAD
	PSE LH5
	PSE LH7
	PSE LX9
	PSE MH5
	PSE MH7
	PSE MV8 TWIN
	PSE 300 2HY
	PSE 300 2VL
	PSE 300 2HD
	PSE 300 VL-RS
	PSE 300 VS
	PSE 300 HD
	AF20
	AF30
	AF75

Parts list

☐ 1x Prefix filter unit

Standard in the system

Option ex factory

Retrofittable

Incompatible